

Modified: December 15, 2014



MATERIAL SAFETY DATA SHEET

For Welding Consumables and Related Products
Essentially Similar to U.S. Department of Labor Form OSHA 20
(to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200)

SECTION I

Identification UNIWELD PRODUCTS, INC. 2850

Supplier Name: Address: Ravenswood Rd., Ft. Lauderdale, FL 33312

Emergency Phone: Call Chemtrec within USA 1-800-424-9300. Outside USA and Canada call 1-703-527-3887

Trade Name: Tungsten (EWP), 2% Ceriated Tungsten (EWCe-2), 2% Lanthanated Tungsten (EWLa-1), 1% Thoriated Tungsten (EWTh-1), 2% Thoriated Tungsten, (EWTh-2), Zirconated Tungsten (EWZr-1), 1.5% Lanthanated Tungsten (EWG)

Classification: AWS A5.12

SECTION II

HAZARDOUS INGREDIENTS/Identity Information

IMPORTANT: This section covers the materials from which the product is manufactured. The fumes and gases produced during welding with the normal use of this product are covered under Section V. Thorium dioxide is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

*The term "HAZARDOUS MATERIALS" should be interpreted as a term required and defined in OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 however the use of this term does not necessarily imply the existence of any hazard.

PRODUCT	W	ZrO ₂	ThO ₂	LaO ₂	CeO ₂
Pure Tungsten	>99.5%	-	-	-	-
Zirconated Tungsten	>99.7%	0.25%	-	-	-
1% Thoriated Tungsten	>98.3%	-	1.2%	-	-
2% Thoriated Tungsten	>97.3%	-	2.2%	-	-
2% Lanthanated Tungsten	>97.3%	-	-	2.2%	-
2% Ceriated Tungsten	>97.3%	-	-	-	2.2%

Occupational Safety and Health Administration 29 CFR 1910.1000 Permissible Exposure Limit (PEL).
American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV[R]
L

SECTION III

Melting Point: Approximately 3400°C Boiling Point:

Approximately 5900°C Vap. Press: N/A at 25°C Vap.

Density: N/A

Radioactive Isotope: Th-232

Solubility in Water: Insoluble

Specific Gravity (H₂O=1): approximately 19

Appearance and odor: Gray, no odor

SECTION IV

Modified: December 15, 2014

FIRE AND EXPLOSION HAZARD DATA

Non-Flammable: Welding arc and sparks can ignite combustibles. See Z-49.1 referenced in Section VI.

SECTION V REACTIVITY DATA

Hazardous Decomposition Products

Welding fumes and gases cannot be classified simply. The composition and quantity of these fumes and gases are dependent upon the metal being welded, the procedures followed and the electrodes used.

Workers should be aware that the composition and quantity of fumes and gases to which they may be exposed, are influenced by: coatings which may be present on the metal being welded (such as paint, plating, or galvanizing), the number of welders in operation and the volume of the work area, the quality and amount of ventilation, the position of the welder's head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing procedure). When the electrode is consumed, the fumes and gas decomposition products generated are different in percent and form from the ingredients listed in Section II. The composition of these fumes and gases are the concerning matter and not the composition of the electrode itself. Decomposition products include those originating from the volatilization, reaction, or oxidation of the ingredients shown in Section II, plus those from the base metal, coating and the other factors noted above.

INGREDIENT	CAS No.	OSHA PEL	ACGIH TWA	ACGIH STEL
Tungsten (W)	7440-33-7	-	5mg/m ³	10mg/m ³
Thorium Dioxide	1314-20-1	-	-	-
Zirconium Oxide	1314-23-4	5mg/m ³	5mg/m ³	10mg/m ³
Cerium Dioxide	1345-13-7	-	-	-
Lanthanum Dioxide	1312-81-8	-	-	-

Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc. One method of determining the composition and quantity of the fumes and gases to which the workers are exposed is to take an air sample from inside the welder's helmet while worn or with the worker's breathing zone. See ANSI/AWS F1.1 publication available from the American Welding Society 55- NW LeJeune Rd. Miami, FL: 33126

SECTION VI HEALTH HAZARD DATA

Threshold Limit Value: The ACGIH recommended general limit for welding fume NOC (Not otherwise classified) is 5 mg/m³. ACGIH1985 preface states: "The TLC-TWA should be used as guides in the control of health hazards and should not be used as fine lines between safe and dangerous concentrations." See section V for specific fume constituents, which may modify this TLV.

Common Entry Is by Inhalation.

Effects of Overexposure: Inhalation of welding fumes and gases can be dangerous to your health. Short-term (acute) overexposure to welding fumes may result in discomfort such as dizziness, nausea, or dryness or irritation of nose, throat, or eyes. Although the inhalation of Tungsten has the potential for causing transient or permanent lung damage, it is generally considered to exhibit a low degree of toxicity. Thorium is a naturally occurring radioactive element. Its primary hazard lies in inhalation of dust/fumes. Normal handling of these electrodes is not expected to result in any significant radiation exposure. Considerable experience in refining and use of thorium has not revealed any adverse effects from industrial exposure. Long-term (chronic) over-exposure to welding fumes can lead to siderosis (iron deposits in lung) and is believed to affect pulmonary function.

Arc Rays can injure eyes and burn skin.

Electric shock can kill. See Section VII.

Emergency and First Aid Procedures: Call for medical assistance. Use first aid procedures recommended by the American Red Cross. If breathing is difficult – give oxygen. If not breathing-use CPR (cardiopulmonary resuscitation).

Carcinogenicity Thorium dioxide has been identified as a carcinogen by NTP, IARC and others. Evidence for its ability to cause cancer has come solely from its internal medical use.

SECTION VII CONTROL MEASURES AND PRECAUTIONS FOR SAFE HANDLING AND USE

Modified: December 15, 2014

Read and understand the manufacturer's instructions and precautionary label on this product. See American Standard Z49.1 Safety in Welding and Cutting, published by the AMERICAN WELDING SOCIETY, 550 N.W. Lejenune Road, Miami, Florida 33126 and OSHA Publication 2206 (29 CFR 1910), U.S.Government Printing Office, Washington D.C. 20402 for more details on the following topics.

Uniweld believes that information set forth in this Material Safety Data Sheet is accurate.

Uniweld makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance therein

Modified: December 15, 2014